

BEST AVAILABLE COPY

Application Number 10/665,086 (Schroeder) GAU 2837 Amendment A continued 2 of 21

Listing of Claims

This listing of claims will replace all prior versions, and listings, of claims in the application. Please amend claims 10, 13, 14, 15, and 18 and cancel claims 16, 17, and 19 as follows:

1. **(ORIGINAL)** A stringed instrument, comprising:

- (a) an elongated body,
- (b) a fingerboard bounded by a nut and a bridge, said fingerboard further having a longitudinal axis,
- (c) one or more strings suspended over said fingerboard between said nut and said bridge,
- (d) a first means for supporting said body on or close to said axis close to or beyond said nut at the chest of a person playing said instrument, and
- (e) a second means for supporting said body on or close to said axis close to or beyond said bridge,

whereby said first and said second means support said fingerboard close to or beyond its two ends, defined by said nut and said bridge, thus ensuring stability of said instrument for left hand operations on said fingerboard and eliminating the need to secure said instrument with the left hand of said person, and
whereby said first and said second means improve rotational stability of said instrument against disturbances of bow operations.

Application Number 10/665,086 (Schroeder) GAU 2837 Amendment A continued 3 of 21

2. **(ORIGINAL)** The stringed instrument of claim 1 wherein said second means supports said body close to said bridge,

whereby said second means reduces the effective weight of said instrument pushing against said person's chest, thus improving playing posture and technique.

3. **(ORIGINAL)** The stringed instrument of claim 1 wherein said first means supports said body at the sternum of said person,

whereby said first means allows positioning of said fingerboard on the anatomical median plane of said person, thus improving playing posture and technique.

4. **(ORIGINAL)** A seat-based instrument-support unit, comprising:

- (a) a support member, a first part of said support member having a first means for interfacing with a seat, said seat bearing said support member, such that said first part of said support member is stationary relative to said seat,
- (b) an instrument having an elongated body, said body having a longitudinal axis,
- (c) a second means for interfacing said support member with said instrument, and
- (d) a third means for restricting rotation of said instrument around said longitudinal axis,

whereby the orientation of said support member, and thus of said instrument, is a function of the orientation of said seat.

Application Number 10/665,086 (Schroeder) GAU 2837 Amendment A continued 4 of 21

5. **(ORIGINAL)** The seat-based instrument-support unit of claim 4 further having a fourth means for rotating said instrument around a second axis, said second axis being perpendicular to the anatomical median plane of a person sitting on said seat and playing said instrument,

whereby said instrument can be rotated around said second axis for adjustment relative to the body of said person.

6. **(ORIGINAL)** The seat-based instrument-support unit of claim 5 wherein said fourth means is a living-hinge design, and wherein said second means is a tongue-and-groove design,

whereby the combination of both said living-hinge design and said tongue-and-groove design enables a secure interface between said support member and said instrument during operation, and

whereby said living-hinge design simplifies construction of said unit, thus economizing production, and

whereby said tongue-and-groove design simplifies construction of said unit, thus economizing production, and

whereby said tongue-and-groove design simplifies both assembly and disassembly of said unit.

7. **(ORIGINAL)** The seat-based instrument-support unit of claim 5 wherein both said fourth means and said second means combined are a magnetic-hinge design,

whereby said magnetic hinge joint eliminates the need for mechanical means of maintaining said interface, thus simplifying construction and reducing production cost; and

Application Number 10/665,086 (Schroeder) GAU 2837 Amendment A continued 5 of 21

whereby the process of joining said body and said support member is assisted
magnetically, and thus simplified, and
whereby the process of separating said body and said support member is simplified.

8. **(ORIGINAL)** The seat-based instrument-support unit of claim 4 further having a fourth means for rotating said instrument around a second axis, said second axis being on or close to the anatomical horizontal plane of a person sitting on said seat and playing said instrument, and on or close to the anatomical median plane of said person,

whereby said instrument can rotate around said second axis congruently with the swaying torso of said person, thus improving playing posture and technique.

9. **(ORIGINAL)** The seat-based instrument-support unit of claim 8 further having a fifth means for spring-like reversion of said instrument to its original position after its rotation around said second axis,

whereby said fourth means and said fifth means emulate the swaying torso motion of said person, thus further improving playing technique.

10. **(CURRENTLY AMENDED)** The seat-based instrument-support unit of claim 9 wherein said fifth means is a torsion-bar design,

~~whereby said torsion-bar design simplifies construction of said unit, thus economizing production.~~

BEST AVAILABLE COPY

Application Number 10/665,086 (Schroeder) GAU 2837 Amendment A continued 6 of 21

11. (ORIGINAL) A support for an instrument, comprising:

- (a) a support member, a first part of said support member having a first means for interfacing with a base, said base bearing said support member, such that said first part of said support member is stationary relative to said base, a second part of said support member having a second means for interfacing with said instrument,
- (b) a primary means for rotating said instrument around a primary axis, said primary axis stationary relative to said first part of said support member, and
- (c) a secondary means for rotating said instrument around a secondary axis, said secondary axis being both perpendicular to said primary axis and stationary relative to said instrument, such that both said secondary axis and said instrument rotate around said primary axis via said primary means,

whereby said secondary means enables adjustment of said instrument, when interfacing with said support member at said second part by said second means, relative to the torso of a musician, and

whereby said primary means enables said instrument, when interfacing with said support at said second part by said second means, to move congruently with the torso motion of said musician, said torso motion defined as swaying within the anatomical coronal plane of said musician; said support is positioned on the anatomical median plane of said musician and perpendicular to the anatomical coronal plane of said musician; and said support is further positioned on or near the anatomical horizontal plane of said musician and aligned with the axis of said torso motion, and

Application Number 10/665,086 (Schroeder) GAU 2837 Amendment A continued 7 of 21

whereby said support prevents rotation of said instrument around the longitudinal axis of said instrument.

12. **(ORIGINAL)** A musical instrument system, comprising:

- (a) a body,
- (b) a support,
- (c) a first means for interfacing said body with the chest of a person,
- (d) a second means for interfacing said body with said support,
- (e) a third means for interfacing said support with a base, said base bearing said support such that a first part of said support is stationary relative to said base, and
- (f) a fourth means for enabling a position change of said body, such that said body can move congruently with the moving torso of said person, while said body interfaces with both said support and said person and while said support interfaces with said base,

whereby the orientation of said body relative to said moving torso of said person is retained, facilitating freedom of torso motion while maintaining constancy of playing technique, independent of the position of said torso.

13. **(CURRENTLY AMENDED)** A stringed instrument, comprising:

- (a) an elongated body having a first end,
- (b) a fingerboard bounded by a nut at or close to said first end and a bridge, said fingerboard further having a longitudinal axis, and

Application Number 10/665,086 (Schroeder) GAU 2837 Amendment A continued 8 of 21

- (c) one or more strings suspended over said fingerboard between said nut and said bridge, the distance between said nut and said bridge greater than that of a viola and less than that of a cello,

whereby said instrument can be played having said axis positioned on the anatomical median plane of a person playing said instrument, and

whereby said instrument can be played having said nut positioned at or close to said person's chest, and

whereby said instrument can be played having the entire length of said fingerboard visible to said person.

~~whereby said instrument can be played having said axis positioned on a person's anatomical median plane, thus enabling more ergonomic posture as well as a more ergonomic playing technique, and~~

~~whereby said nut can be positioned on or close to said person's chest thus creating a more ergonomic left hand position, and~~

~~whereby the position of said bridge enables ergonomic bow arm operations.~~

14. (CURRENTLY AMENDED) A non-fretted stringed instrument with non-traditional nut, comprising:

- (a) a fingerboard having a longitudinal axis, and
- (b) a nut positioned non-perpendicular to said axis ~~and aligned with the orientation of a player's fingering hand while said hand is ergonomically approaching said nut,~~
at an angle predetermined by the preference of a person playing said instrument.

Application Number 10/665,086 (Schroeder) GAU 2837 Amendment A continued 9 of 21

whereby said nut alters the traditional fingerboard topology close to said nut in
accordance with the preference of said person playing said instrument.

~~whereby said nut creates a more ergonomic fingerboard topology when said hand
approaches said nut.~~

15. **(CURRENTLY AMENDED)** A non-fretted stringed instrument with non-traditional bridge,
comprising:

- (a) a fingerboard having a longitudinal axis, and
- (b) a bridge positioned non-perpendicular to said axis ~~and aligned with the orientation
of a player's fingering hand while said hand is ergonomically approaching said
bridge, at an angle predetermined by the preference of a person playing said
instrument.~~

whereby said bridge alters the traditional fingerboard topology close to said bridge in
accordance with the preference of said person playing said instrument.

~~whereby said bridge creates a more ergonomic fingerboard topology when said hand
approaches said bridge, and~~

~~whereby said bridge substantially aligns known points of contact, thus simplifying the
bowing technique of said instrument.~~

16. **(CANCELED)**

17. **(CANCELED)**

Application Number 10/665,086 (Schroeder) GAU 2837 Amendment A continued 10 of 21

18. **(CURRENTLY AMENDED)** A stringed instrument with geared tuning system, comprising:

- (a) a body,
- (b) a rotatable peg for tuning a string,
- (c) a rotatable wheel having an outer rim, ~~said outer rim having means for providing friction, and~~
- (d) a gear operatively connecting said peg and said wheel such that rotation of said wheel results in rotation of said peg, said gear further having a ratio sufficient to enable tuning of said string by sliding a finger tangentially along said outer rim, whereby pitch perception, being linear, is translated into an analogous linear finger movement, resulting in more intuitive tuning, and whereby said linear finger movement provides an ergonomic alternative to traditional tuning movements;
whereby said string may be tuned by sliding a finger tangentially along the rim of said wheel, resulting in linear tuning motion.

19. **(CANCELED)**

20. **(NEW)** A stringed instrument, comprising:

- (a) an elongated body,
- (b) a fingerboard bounded by a nut and a bridge, said fingerboard further having a longitudinal axis,
- (c) one or more strings suspended over said fingerboard between said nut and said bridge,

Application Number 10/665,086 (Schroeder) GAU 2837 Amendment A continued 11 of 21

(d) a first support for supporting said body on or close to said axis close to or beyond said nut, the non-fingerboard side of said nut, at the chest of a person playing said instrument, and

(e) a second support for supporting said body on or close to said axis close to or beyond said bridge, the non-fingerboard side of said bridge,

whereby said first and said second supports support said fingerboard close to or beyond its two ends, defined by said nut and said bridge, thus ensuring stability of said instrument for left hand operations on said fingerboard and eliminating the need to secure said instrument with the left hand of said person, and

whereby said first and said second supports improve rotational stability of said instrument against disturbances of bow operations.

21. (NEW) The stringed instrument of claim 20 wherein said second support supports said body close to said bridge,

whereby said second support reduces the effective weight of said instrument pushing against said person's chest, thus improving playing posture and technique.

22. (NEW) The stringed instrument of claim 20 wherein said first support supports said body at the sternum of said person,

whereby said first support allows positioning of said fingerboard on the anatomical median plane of said person, thus improving playing posture and technique.

Application Number 10/665,086 (Schroeder) GAU 2837 Amendment A continued 12 of 21

23. (NEW) A seat-based instrument-support unit, comprising:

- (a) a support member, a first part of said support member having a first connector for interfacing with a seat, said seat bearing said support member, such that said first part of said support member is stationary relative to said seat,
- (b) an instrument having an elongated body, said body having a longitudinal axis, and
- (c) a second connector for interfacing said support member with said instrument such that it restricts rotation of said instrument around said longitudinal axis,

whereby the orientation of said support member, and thus of said instrument, is a function of the orientation of said seat.

24. (NEW) The seat-based instrument-support unit of claim 23 further having a pin joint for rotation of said instrument around a second axis, said second axis being perpendicular to the anatomical median plane of a person sitting on said seat and playing said instrument,

whereby said instrument can be rotated around said second axis for adjustment relative to the body of said person.

25. (NEW) The seat-based instrument-support unit of claim 24 wherein said second axis is on or close to the anatomical horizontal plane of said person.

26. (NEW) The seat-based instrument-support unit of claim 23 further having a pin joint for rotating said instrument around a second axis, said second axis being on or close to the anatomical median plane and perpendicular to the anatomical coronal plane of said person.

Application Number 10/665,086 (Schroeder) GAU 2837 Amendment A continued 13 of 21

27. (NEW) The seat-based instrument-support unit of claim 26 wherein said second axis is on or close to the anatomical horizontal plane of a person sitting on said seat and playing said instrument,

whereby said instrument can rotate around said second axis congruently with the swaying torso of said person, thus improving playing posture and technique.

28. (NEW) The seat-based instrument-support unit of claim 26 further having a "spring" system for spring-like reversion of said instrument to its original position after its rotation around said second axis.

29. (NEW) A support for an instrument with elongated body, comprising:

- (a) a support member, a first part of said support member having a first connector for interfacing with an instrument, a second part of said support member having a second connector for interfacing with a base, said base bearing said support member, such that said second part of said support member is stationary relative to said base,
- (b) a primary pin joint for rotating said instrument around a primary axis, said primary axis stationary relative to said first part of said support member, said primary axis also substantially intersecting with the longitudinal axis of said instrument, and
- (c) a secondary pin joint for rotating said instrument around a secondary axis, said secondary axis being both perpendicular to said primary axis and stationary relative to said instrument, such that both said secondary axis and said instrument

Application Number 10/665,086 (Schroeder) GAU 2837 Amendment A continued 14 of 21

rotate around said primary axis via said primary pin joint, said secondary axis also being perpendicular to the longitudinal axis of said instrument, and said secondary axis also substantially intersecting with the longitudinal axis of said instrument,

whereby said secondary pin joint enables adjustment of said instrument, when interfacing with said support member via said first connector, relative to the torso of a musician, and

whereby said primary pin joint enables said instrument, when interfacing with said support via said first connector, to move congruently with the torso motion of said musician, said torso motion defined as swaying within the anatomical coronal plane of said musician; said support is positioned having said primary axis on the anatomical median plane and perpendicular to the anatomical coronal plane of said musician; and said support is further positioned having said primary axis on or near the anatomical horizontal plane of said musician and aligned with the axis of said torso motion, and

whereby said support prevents rotation of said instrument around the longitudinal axis of said instrument.

30. (NEW) The support of claim 29 wherein said primary axis and said secondary axis intersect substantially.

Application Number 10/665,086 (Schroeder) GAU 2837 Amendment A continued 15 of 21

31. (NEW) A musical instrument system, comprising:

- (a) an instrument body,
- (b) a support,
- (c) a rest for interfacing said body with the chest of a person,
- (d) a first connector for interfacing said body with said support,
- (e) a second connector for interfacing said support with a base, said base bearing said support such that a part of said support is stationary relative to said base, and
- (f) a pivot system for enabling a position change of said body, such that said body can move congruently with the moving torso of said person, while said body interfaces with both said support and said person and while said support interfaces with said base,

whereby the orientation of said body relative to said moving torso of said person is retained, facilitating freedom of torso motion while maintaining constancy of playing technique, independent of the position of said torso.

32. (NEW) A stringed instrument with non-traditional nut-bridge orientation, comprising:

- (a) a fingerboard having a longitudinal axis,
- (b) a nut positioned non-perpendicular to said axis, at an angle predetermined by the preference of the person playing said instrument, and
- (c) a bridge positioned parallel to said nut,

whereby the non-traditional orientation of said nut and said bridge alters the traditional fingerboard topology in accordance with the preference of said person playing said instrument.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.